Docket No.: CISCO-4113

In the claims:

 (Previously Presented) A method for measuring the performance of a scalable network comprising:

preparing a network under test for testing;

establishing a routing path for a session to be tested wherein said routing path is a static IP route;

sending, by a packet generator at a first end of said Static IP route, a constant stream of packets through a network under test;

counting, by a packet count unit, received packets at the packet count unit at a second end of said static IP route; and

establishing a peak performance rate as the highest rate with no packet dropout.

## 2-4. (Cancelled)

- (Original) The method of claim 1, wherein said act of sending a constant stream of packets includes the act of sending said constant stream of packets over an OC-3 level network.
- (Original) The method of claim 1, wherein said act of sending a constant stream of packets includes the act of sending said constant stream of packets over an OC-12 level network.
- (PreviouslyPresented) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to

perform a method for measuring the performance of a scalable network, said method comprising:

preparing the network for testing;

establishing a routing path for a session to be tested wherein said routing path is a static IP route a server at a first end of said route and a client node at a second end of said route:

sending, by a server, a constant stream of packets to a client node; counting, by said client node, said packets received at said client node; and

establishing a peak performance rate as the highest rate with no packet dropout.

## 8-10. (Cancelled)

- 11. (Original) The program storage device of claim 7, wherein said act of sending a constant stream of packets includes the act of sending said constant stream of packets over an OC-3 level network.
- 12. (Original) The program storage device of claim 7, wherein said act of sending a constant stream of packets includes the act of sending said constant stream of packets over an OC-12 level network.
- (Previously Presented) An apparatus for measuring the performance of a scalable network comprising:

means for preparing the network for testing;

means for establishing a routing path for a session to be tested wherein said routing path is a static IP route having a server at a first end of said route and a client node at a second end of said route; means in a server for sending a constant stream of packets to a client node;

means in said client node for counting said packets received by said client
node; and

means for establishing a peak performance rate as the highest rate with no packet dropout.

## 14-16. (Cancelled)

- 17. (Original) The method of claim 13, means for sending a constant stream of packets includes the act of sending said constant stream of packets over an OC-3 level network.
- 18. (Original) The method of claim 13, means for sending a constant stream of packets includes the act of sending said constant stream of packets over an OC-12 level network.
- (Previously Presented) A system for measuring the performance of a scalable network comprising:

a packet generator in a source node at a first end of a static IP route for providing test packets to a network under test;

a packet count unit in a client node at a second end of said static IP route for counting test packets received by said client node from said network under test; and wherein said test packets are provided in a constant stream to said

network under test and wherein a peak performance rate of said network under test is established as the maximum receive rate at a particular packet size with no packet dropout.

Docket No.: CISCO-4113

 (Original) The system of claim 19, wherein said network under test comprises a OC-3 level network.

21. (Original) The system of claim 19, wherein said network under test comprises a OC-12 level network.

## 22-24.(Cancelled)

- (Original) The system of claim 20, wherein said network under test includes two Fast Ethernet pathways.
- (Original) The system of claim 21, wherein said network under test includes eight Fast Ethernet pathways.
- (Original) The system of claim 21, wherein said network under test includes at least two Gigabit Ethernet pathways.
- (Original) The system of claim 21, wherein said network under test includes four OC-3 pathways.
- (Original) The system of claim 19, wherein said packet generator is configured using Pagent software.
- (Original) The system of claim 19, wherein said system is configured to download a test configuration file from a TFTP server.